

SQUARE® LSR8602-50A/B

Silicone Rubber, LSR

Shenzhen SQUARE Silicone Co., Ltd.

Message:

Coating silicone for automobile airbag

Product description

The mixture of the two parts is used for manufacturing silicone resin insulating varnish such as silicone glass cloth, tube etc, it can form high temperature-resistant thin membrane with good rebound property, it has the dampproof, fireproof, sealing and insulative effects, the insulative function can be kept though the dipped insulative products are bended.

Key Features

Fire-proof, damp-proof, sealing and insulative effects, the insulative function can be kept though the dipped insulative products are bended.

Application

Coating silicone for airbag of autos

General Information			
Features	Heat resistance, high Flame retardancy		
Uses	Application in Automobile Field Coating application		
Appearance	Clear/transparent		
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	1.0E+15	ohms·cm	IEC 60093
Thermoset	Nominal Value	Unit	Test Method
Pot Life	4300	min	
Shelf Life	52	wk	
Uncured Properties	Nominal Value	Unit	Test Method
Solids Content	> 30	%	
Viscosity	2.0 - 2.5	Pa·s	DIN 53019

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

