

DOW™ HDPE 82054T

High Density Polyethylene Resin

The Dow Chemical Company

Message:

For injection molding applications

For cap and closure, household products and toys

Complies with:

U.S.FDA 21 CFR 177.1520 (c) 3.2A

Europe: Commission Regulation (EU) No 10/2011

Consult the regulations for complete details.

General Information			
Agency Ratings		EU No 10/2011	
		FDA 21 CFR 177.1520(c) 3.2a	
Forms		Pellets	
Processing Method		Injection Molding	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.954	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

