

Braskem PP FF018F

Polypropylene Homopolymer

Braskem America Inc.

Message:

Excellent color and processing stability, superior optical and mechanical properties, broad processing window

Applications

Suggested uses include BOPP applications

General Information			
Features	Optical		
	Good processing stability		
	Good coloring		
Agency Ratings		FDA 21 CFR 177.1520	
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.8	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	33.8	MPa	ASTM D638
Flexural Modulus - 1% Secant ²	1310	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	27	J/m	ASTM D256A
NOTE			
1.	51 mm/min		
2.	1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

