

# DuraFlex 889-2

Thermoplastic Polyurethane Elastomer (Polyester)

Evermore Chemical Industry Co., Ltd.

## Message:

DuraFlex 889-2 is a Thermoplastic Polyurethane Elastomer (Polyester) (TPU-Polyester) product. It is available in Asia Pacific. Typical application: Consumer Goods.

General Information			
Uses	Footwear		
Physical	Nominal Value	Unit	Test Method
Density	0.420 to 0.450	g/cm <sup>3</sup>	ASTM D1505
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C)	77 to 83		ASTM D2240
Additional Information	Nominal Value	Unit	
Composition	889-1A+889-2BYE		
Moulding Times	6.0 to 7.0	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT