INEOS PP 100-NB03

Polypropylene Homopolymer

INEOS Olefins & Polymers Europe

Message:

100-NB03 is a polypropylene grade intended for sheet extrusion and thermoforming applications requiring improved transparency and higher stiffness than conventional polypropylene. It is nucleated and clarified but does not contain any antistatic agent. It offers a good balance between easy flow and mechanical properties and features very good optical properties and good thermal stability of end products. Applications

Beer cups

Transparent trays for biscuits, fruit and vegetables Containers for various food products Benefits and Features Very good optical properties High stiffness of end products Moderate foaming (beer cups) Good thermal stability Easy processing in both forming and cutting

General Information				
Additive	Clarifier			
	Nucleating Agent			
Features	Good Flow			
	Good Processability			
	Good Thermal Stability			
	High Stiffness			
	Homopolymer			
	Nucleated			
	Opticals			
Uses	Containers			
	Cups			
	Food Containers			
RoHS Compliance	Contact Manufacturer			
Processing Method	Sheet Extrusion			
	Thermoforming			
Physical	Nominal Value	Unit	Test Method	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	3.0	g/10 min	ISO 1133	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Stress (Yield)	39.0	MPa	ISO 527-2	
Flexural Modulus (23°C)	1800	MPa	ISO 178	

Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	3.0	kJ/m²	ISO 180/1A
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	156	°C	ISO 306/A
Peak Melting Temperature	165	°C	ASTM D3417
Peak Crystallization Temperature (DSC)	129	°C	ASTM D3417

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

