

TABOND 2003

Ethylene-based Plastomer

SILON s.ro

Message:

TABOND 2003 is a ethylene-octene copolymer modified with maleic anhydride functional groups.

General Information			
Features	Copolymer Durable Good Adhesion		
Uses	Adhesives Blow Molding Applications Bonding Metal Bonding Plastics Modification Tubing		
Appearance	White		
Forms	Pellets		
Processing Method	Blow Molding Coextrusion		
Physical	Nominal Value	Unit	
Density	0.880	g/cm ³	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.5	g/10 min	
Hardness	Nominal Value	Unit	
Shore Hardness (Shore A, 15 sec)	72		
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	65.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

