# STARFLEX® D 2265

### Thermoplastic Elastomer

STAR Thermoplastic Alloys & Rubbers, Inc.

### Message:

STARFLEX® D 2265 is a Thermoplastic Elastomer (TPE) material. It is available in North America for extrusion or injection molding. Typical application of STARFLEX® D 2265: Engineering/Industrial Parts

| General Information |                   |
|---------------------|-------------------|
| Features            | General Purpose   |
| Uses                | Gaskets           |
| Appearance          | Natural Color     |
| Forms               | Pellets           |
| Processing Method   | Extrusion         |
|                     | Injection Molding |

| Physical                     | Nominal Value | Unit  | Test Method |
|------------------------------|---------------|-------|-------------|
| Specific Gravity             | 1.01          | g/cm³ | ASTM D792   |
| Molding Shrinkage - Flow     | 0.30 to 0.50  | %     | ASTM D955   |
| Hardness                     | Nominal Value | Unit  | Test Method |
| Durometer Hardness (Shore A) | 65            |       | ASTM D2240  |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

