

MIDILENA III HDPE6205B

High Density Polyethylene

ROMPETROL PETROCHEMICALS S.R.L.

Message:

MIDILENA III HDPE6205B is a High Density Polyethylene product. It can be processed by blow molding and is available in Europe. Typical application: Bottles.

Characteristics include:

Antioxidant

Chemical Resistant

General Information			
Additive	Antioxidant Halogen		
Features	Antioxidant Good Chemical Resistance Halogenated		
Uses	Bottles		
Forms	Pellets		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.35	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

