

Viton® B-910

Fluoroelastomer
DuPont Performance Elastomers

Message:

Viton® B-910 is a Fluoroelastomer product. It is available in Europe or North America. Applications of Viton® B-910 include automotive, packaging and sealing applications.
Characteristics include:
Chemical Resistant
Corrosion Resistant
Wear Resistant

General Information			
Features	Acid Resistant		
	Fungus Resistant		
	Gasoline Resistance		
	Good Abrasion Resistance		
	Good Corrosion Resistance		
	Low Gas Permeability		
	Oil Resistant		
	Oxidation Resistant		
Uses	Automotive Under the Hood		
	Packaging		
	Seals		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.85	g/cm³	ASTM D792
Apparent Density	1.85	g/cm³	ASTM D1895
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	77		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	14.5	MPa	ASTM D412
Tensile Elongation (Break)	200	%	ASTM D412
Compression Set (200°C)	25	%	ASTM D395

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

