

InSphere® 1640F

Expanded Polystyrene

Synthos S.A.

Message:

InSphere® type 0513F, 0814F and 1020F is self-extinguishing expandable polystyrene (EPS) with a reduced thermal conductivity.

The materials are formed by spherical polystyrene particles that contain a flame retardant system and a hydrocarbon blowing agent. Their surface is treated against gluing during processing and the formation of electrostatic charge. Due to the content of halogenated flame retardant and the residual blowing agent, the product is unsuitable for objects intended for direct contact with food.

InSphere® 1020F, 1640F is mainly used for production of high volume blocks with low-density; of cutted boards and profiles from the blocks for a thermal insulation e.g. building objects.

General Information			
Additive	Blowing Agent Flame Retardant		
Features	Flame Retardant Halogenated Self Extinguishing		
Uses	Insulation Profiles		
Appearance	White		
Forms	Spheres		
Physical	Nominal Value	Unit	Test Method
Apparent Density ¹	0.02 to 0.04	g/cm ³	Internal Method
Moisture Content	< 10000	ppm	Internal Method
Particle Size - >95% between	1.60 to 4.00	mm	Internal Method
Reaction to Fire			
--	B1		DIN 4102
--	Class E		EN 13501-1
Blowing Agent	< 7.0	wt%	Internal Method
NOTE			

1.

The typical bulk density indicates values obtained during single-step pre-foaming on continuous pre-foaming devices. Lower values of bulk density can be achieved only after multiple pre-expansion.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

