

PETILEN F2-12

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

PETILEN F2-12 is a Low Density Polyethylene product. It can be processed by film extrusion and is available in Asia Pacific, Europe, or North America. Applications of PETILEN F2-12 include film and packaging.

General Information			
Features	General Purpose		
Uses	Film		
	General Purpose		
	Packaging		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.918 to 0.922	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0 to 3.0	g/10 min	ASTM D1238
Ash Content ¹	0.1	wt%	
Film Quality ²	A		
Optical	Nominal Value	Unit	Test Method
Gloss	70		ASTM D2457
Haze	6.3	%	ASTM D1003
NOTE			
1.	ALKT-509		
2.	ALKATHENE 36		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT