

Gravi-Tech™ GRV-UR-060-W-BLK

Polyurethane

PolyOne Corporation

Message:

Gravi-Tech™ GRV-UR-060-W-BLK is a Polyurethane product. It can be processed by injection molding and is available in North America. Applications of Gravi-Tech™ GRV-UR-060-W-BLK include industrial applications, medical/healthcare and sporting goods. Primary characteristic: non-toxic.

General Information			
Features	High Density Non-Toxic		
Uses	Industrial Applications Medical/Healthcare Applications Projectiles Sporting Goods Weighting & Balancing		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	5.99	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.60 to 0.90	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 10 sec)	50		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	214	MPa	ASTM D790
Flexural Strength ¹ (Yield)	9.47	MPa	ASTM D790
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	14.0	MPa	ASTM D412
Tensile Strength (Yield)	14.3	MPa	ASTM D412
Tensile Elongation ² (Break, 23°C)	200	%	ASTM D412
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	390	J/m	ASTM D256
NOTE			
1.	13 mm/min		
2.	510 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

