

Nylene® 6234 HS

Polyamide 6

Custom Resins Group

Message:

Nylene® 6234 HS is a Polyamide 6 (Nylon 6) material filled with 34% mineral. It is available in North America for extrusion or injection molding.

Important attributes of Nylene® 6234 HS are:

Good Dimensional Stability

Good Stiffness

Heat Stabilizer

High Strength

General Information	
Filler / Reinforcement	Mineral,34% Filler by Weight
Additive	Heat Stabilizer
Features	Good Dimensional Stability
	Good Stiffness
	Heat Stabilized
	High Strength
Forms	Pellets
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.43	g/cm ³	ASTM D792
Molding Shrinkage - Flow	1.0	%	ASTM D955
Thermal	Nominal Value	Unit	
Melting Temperature	216	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT