YUPLENE® B380G

Polypropylene Impact Copolymer

SK Global Chemical

Message:

YUPLENE B380G is a propylene impact copolymer designed for injection molding applications. YUPLENE B380G has high stiffness, excellent dimensional stability, good impact strength and has been listed by Underwriters Laboratories (UL). YUPLENE B380G is especially suitable for various electrical appliances such as washing machine parts and refrigerator parts.

General Information					
UL YellowCard	E135809-222660				
Features	Good Dimensional Stability				
	Good Impact Resistance				
	High Flow				
	High Stiffness				
	Impact Copolymer				
Uses	Appliance Components				
	Automotive Applications				
	Containers				
	Electrical/Electronic Applications				
	Industrial Applications				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	28	g/10 min	ASTM D1238		
Spiral Flow	> 80.0	cm	Internal Method		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	90		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	25.5	МРа	ASTM D638		
Tensile Elongation (Break)	< 300	%	ASTM D638		
Flexural Modulus	1180	МРа	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	44	J/m			
23°C	88	J/m			
Aging	Nominal Value	Unit	Test Method		
Accelerated Oven Aging - in Air (150°C)	15.0	day	ASTM D3012		
Heat Deflection Temperature	110	°C	ASTM D648		
DuPont Impact Strength (-10°C)	> 6.86	J	ASTM D2794		

Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

