

SIMONA® PVC-CAW

Rigid Polyvinyl Chloride

SIMONA AMERICA, Inc.

Message:

SIMONA® PVC-CAW is a Rigid Polyvinyl Chloride product. It is available in Europe, Latin America, or North America. Primary characteristic: flame rated.

General Information			
UL YellowCard	E156995-223985		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.44	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Shore Hardness	82		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	3300	MPa	ASTM D638
Tensile Strength (Yield)	57.9	MPa	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	66.1	°C	ASTM D648
CLTE - Flow	8.0E-5	cm/cm/°C	ASTM D696
Flammability	Nominal Value		Test Method
Flame Rating (1.00 mm)	V-0		UL 94
Additional Information	Nominal Value	Unit	
Operating Temperature	0 to 60	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT