

# Manner Flexible PVC X3498

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

## Message:

Recommended Applications: Lead-free general purpose fungus resistant transparent compound. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive.

General Information			
Additive	Antimicrobial (Fungicide)		
Features	Fungus Resistant		
	General Purpose		
	Low (to None) Lead Content		
Uses	General Purpose		
Appearance	Clear/Transparent		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.19 to 1.23	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	79 to 85		
Shore A, 15 sec	74 to 80		
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant <sup>1</sup>	7.21	MPa	ASTM D638
Tensile Strength <sup>2</sup>	16.1	MPa	ASTM D638
Tensile Elongation <sup>3</sup> (Break)	400	%	ASTM D638
NOTE			
1.	Unaged Dumbbells: .06 inch		
2.	Unaged Dumbbells: .06 inch		
3.	Unaged Dumbbells: .06 inch		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT