

# EPAMOULD 295A10T

Thermoplastic Polyurethane Elastomer (Polyester)

Epaflex Polyurethanes S.R.L.

## Message:

EPAMOULD 295A10T is a thermoplastic polyurethane elastomer (polyester)(TPU-polyester) product. It can be processed by extrusion or injection molding and is available in Europe.

Features include:

High Flexibility

high strength

accessible food

General Information	
Additive	Beeswax
Features	High Flexibility
	High strength
	Hydrolysis resistance
	Compliance of Food Exposure
Appearance	Multi-Colored
Processing Method	Extrusion
	Injection molding

Physical	Nominal Value	Unit
Density	1.19	g/cm <sup>3</sup>
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	95	
Mechanical	Nominal Value	Unit
Abrasion Loss	35.0	mm <sup>3</sup>

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT