

# HYBRANCH HP-700

Specialty Polystyrene

DIC Corporation

## Message:

HYBRANCH HP-700 is a Specialty Polystyrene product. It can be processed by extrusion and is available in Asia Pacific or North America. Typical application: Sheet.

General Information			
Uses	Microfoamed Sheet		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.04 to 1.05	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR)	3.0	g/10 min	ISO 1133
Molding Shrinkage	0.40 to 0.80	%	ISO 294-4
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	67		ISO 2039-2
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	53.0	MPa	ISO 527-2
Tensile Strain (Break)	2.0	%	ISO 527-2
Flexural Modulus	3300	MPa	ISO 178
Flexural Stress	103	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	2.0	kJ/m <sup>2</sup>	ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	102	°C	ISO 306

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

