

CGPC PVC R-10X NI Extrusion

Flexible Polyvinyl Chloride
China General Plastics Corporation

Message:
CGPC PVC R-10X NI Extrusion is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific or North America for extrusion.
Typical application of CGPC PVC R-10X NI Extrusion: Electrical/Electronic Applications

General Information			
Uses	Electrical/Electronic Applications		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.37	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	59.8	MPa	ASTM D638
Tensile Elongation (Break)	60	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (Area)	1.96	kJ/m ²	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	90.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT