

# SynPlast™ DOP-N

Di (2-ethylhexyl) Phthalate

PolyOne Corporation

Message:

Branched C8 phthalate ester

General Information			
Features	General Purpose		
Uses	General Purpose		
Appearance	Clear/Transparent		
Forms	Liquid		
Processing Method	Compounding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity <sup>1</sup>	0.978 to 0.984	g/cm <sup>3</sup>	ASTM D4052
Acid Number - Maximum	0.07	mg KOH/g	ASTM D1045
Appearance	Clear, clean		ASTM D2090
Color <sup>2</sup>	25		ASTM D1209
Ester Content - Minimum	99	%	ASTM D3465
Molecular Weight <sup>3</sup>	390		
Vapor Pressure (200°C)	1.60E-4	MPa	
Viscosity - Kinematic (25°C)	58.0	cSt	ASTM D445
Water Content - Maximum	1000	ppm	ASTM D1533
Pour Point	-47	°C	
Refractive Index (25°C)	1.4852		
NOTE			
1.	25/25°C		
2.	Pt-Co Scale, Maximum		
3.	Theoretical		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT