

SCHULAMID® 66GF43HRN

Polyamide 66

A. Schulman Inc.

Message:

Nylon 66 43% Glass Fiber Industrial Grade

General Information			
Filler / Reinforcement	Glass Fiber,43% Filler by Weight		
Recycled Content	Yes		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.52	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	192	MPa	ISO 527-2/5
Flexural Modulus ¹	14800	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength	9.5	kJ/m ²	ISO 180
Additional Information	Nominal Value	Unit	Test Method
Filler Content	45	%	ASTM D5630
NOTE			
1.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT