Nycast 612VS C-85

Polyamide 612

Cast Nylons Ltd.

Message:

Nycast 612VS C-85 is a Polyamide 612 (Nylon 612) material. It is available in North America for casting. Typical applications include: Engineering/Industrial Parts
Seating

General Information			
Uses	Seats		
	Valves/Valve Parts		
Appearance	Yellow		
Forms	Pellets		
Processing Method	Casting		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.10	g/cm³	ASTM D792
Water Absorption			ASTM D570
24 hr	0.30	%	
Saturation	4.0	%	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	81		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1650	MPa	ASTM D638
Tensile Strength (Yield)	60.0	MPa	ASTM D638
Tensile Elongation (Yield)	25	%	ASTM D638
Flexural Modulus	1970	MPa	ASTM D790
Flexural Strength (Yield)	103	MPa	ASTM D790
Shear Strength	52.4	MPa	ASTM D732
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	48	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	98.9	°C	ASTM D794
Melting Temperature	210	°C	
CLTE - Flow	7.0E-5	cm/cm/°C	ASTM D696

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

