

SQUARE® LIM6934-54A/B

Silicone Rubber, LSR
Shenzhen SQUARE Silicone Co., Ltd.

Message:

Foam liquid silicone rubber for OA roller

Product Description

The product is one kind of 2-part silicone rubber, catalyzed by platinum, mainly used in printer and duplicating machine roller surface material, suitable for injection moulding processes.

Key Features

High rebound, low volatility, high temperature resistance

At the temperature of 20°C and in the condition of air-proof, the shelf life is 5 days after mixing A and B, the shelf life will decrease with the increasing of the temperature.

Application

The product is mainly used in printer and duplicating machine roller surface material.

General Information			
Features	Foamable property		
	Heat resistance, high		
Uses	Roller		
	Printing machine parts		
Appearance	Red		
Processing Method	Liquid Injection Molding (LIM)		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	36		ASTM D2240
Thermoset	Nominal Value	Unit	Test Method
Pot Life (20°C)	7200	min	
Shelf Life	52	wk	
Uncured Properties	Nominal Value	Unit	Test Method
Viscosity	70	Pa·s	DIN 53019
Cured Properties	Nominal Value	Unit	Test Method
Rebound Resilience	75	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT