

# MTEGRITY™ LDPE LD700

Low Density Polyethylene

M. Holland Company

Message:

MTEGRITY™ LDPE LD700 is a Low Density Polyethylene product. It can be processed by injection molding and is available in North America. Typical application: Caps/Lids/Closures.  
Characteristics include:  
Clarity  
Good Processability  
High Flow  
Warp Resistant

General Information			
Features	Good Processability		
	High Clarity		
	High Flow		
	Narrow Molecular Weight Distribution		
	Warp Resistant		
Uses	Caps		
	Lids		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.922	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	35	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	50		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	11.0	MPa	ASTM D638
Tensile Elongation (Break)	110	%	ASTM D638
Flexural Modulus	276	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-39.4	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

