

Vistalon™ 2502

Ethylene Propylene Diene Terpolymer Rubber

ExxonMobil Chemical

Message:

Vistalon 2502 EPDM is a low Mooney polymer with low ethylene content and medium diene content. It has a wide molecular weight distribution and can achieve excellent combination processability, even without adding plasticizers. It is suitable for brake parts, precision seals, gaskets, molded foam sheets, electrical connectors, hose spindles and other molded articles. It can also be used as a polymeric plasticizer in mixtures of other high-viscosity polymers.

General Information			
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity ¹ (ML 1+4, 125°C)	26	MU	ASTM D1646
Ethylene Content	49.0	wt%	ASTM D3900
Ethylidene Norbornene (ENB) Content	4.2	wt%	ASTM D6047

Legal statement

未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或有关详细的产品监管信息,请联系客户服务.

NOTE

1.
- Radial cavity mold, polymer
re-refined at 145±10°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

