

# Caltex PP H430

Polypropylene Homopolymer

GS Caltex

Message:

Caltex PP H430 is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific.

Important attributes of Caltex PP H430 are:

High Strength

Homopolymer

Typical application of Caltex PP H430: Adhesives/Tapes

General Information			
Features	Good Stretchability		
	High Strength		
	Homopolymer		
Uses	Tape		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.903	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.5	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.5 to 1.9	%	
Across Flow	1.5 to 1.9	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	104		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	36.3	MPa	ASTM D638
Tensile Elongation			ASTM D638
Yield	10	%	
Break	> 500	%	
Flexural Modulus	1470	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	31	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	123	°C	ASTM D648
Vicat Softening Temperature	152	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

