Propafilm™ RK140

Polypropylene Alloy Innovia Films Ltd.

Message:

Heat Sealable Anti-Mist Coated Film

Biaxially oriented polypropylene (BOPP) film coated with two aqueous dispersions of polyvinylidene chloride (PVdC) copolymer.

RK100/120/140 are recommended for use as a single web in the salad industry. Particularly suited for medium to large packs on formfill-seal machines.

General Information				
Features	Antistatic			
	Excellent Printability			
	Food Contact Acceptable			
	Good Weather Resistance			
	Heat Sealable			
	High Gloss			
	Low Moisture Vapor Transmission			
Uses	Bi-axially Oriented Film			
	Food Packaging			
	Food Service Applications			
	Packaging			
	, ackaging			
Forms	Film			
Physical	Nominal Value	Unit	Test Method	
Molding Shrinkage			Internal Method	
Flow: 121°C, 1 min	4.0	%		
Flow: 129°C, 1 min	7.0	%		
Across Flow: 129°C, 1 min	4.0	%		
Mechanical	Nominal Value	Unit	Test Method	
Coefficient of Friction			ASTM D1894	
vs. Itself - Dynamic	0.25			
vs. Itself - Static	0.25			
Films	Nominal Value	Unit	Test Method	
Film Thickness - Tested	3600	μm		
Seal Strength ¹	0.15	N/mm	Internal Method	
Seal Initiation Temperature ²	90.6 to 146	°C	Internal Method	
Oxygen Permeability (25°C, 0% RH)	0.63	cm³·mm/m²/atm/24 hr	ASTM F1927	
Water Vapor Transmission Rate (38°C, 90% RH)	4.5	g/m²/24 hr	ASTM F1770	
Yield	29.1	m²/kg	Internal Method	
Optical	Nominal Value	Unit	Test Method	

Gloss (45°)	100		ASTM D2457	
Haze ³	3.0	%	ASTM D1003	
NOTE				
1.	265°F; 1sec; 15lb/in²	265°F; 1sec; 15lb/in²		
2.	2secs; 15psi	2secs; 15psi		
3.	Wide angle; 2.5°			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

