

Sanren EVA 15/2

Ethylene Vinyl Acetate Copolymer
SINOPEC Shanghai Petrochemical Co. Ltd.

Message:

The product is a colourless oblate pellet with excellent chemical stability, flexibility and adhesion properties. It possesses certain impact resistance, good stress-fracture resistance and fine light transmittance.
Scope of Application: Expanded plastic product

General Information	
Features	High Light Transmission
	High ESCR (Stress Cracking Resistance)
	Copolymer
	Impact resistance, good
	Good flexibility
	Good adhesion
Appearance	Colorless
Forms	Particle
Processing Method	Blow molding
	Extrusion
	Injection molding

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	1.3 - 2.7	g/10 min	Internal method
Vinyl Acetate Content	13.5 - 16.5	wt%	

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	> 8.00	MPa	Internal method
Tensile Elongation (Break)	> 600	%	Internal method

Additional Information	Nominal Value
Hue	
Cleanliness: <40 pieces/kg	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT