

# VESTOLIT® M 5761

Polyvinyl Chloride  
VESTOLIT GmbH & Co. KG

Message:

VESTOLIT M 5761 - is a free-flowing mass(M) PVC with a narrow particle size distribution. It is suitable for extrusion, injection moulding, calendering and powder coating.

General Information	
Features	Foamable
	Homopolymer
	Low Viscosity
Uses	Bottles
	Containers
	Film
	Piping
	Profiles
	Sheet
Forms	Powder
Processing Method	Blow Molding
	Calendering
	Coating
	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Apparent Density	0.61	g/cm³	ISO 60
K-Value	57.0		ISO 1628-2
Sieve Analysis			ISO 4610
-- 1	< 2.0	%	
-- 2	> 93	%	
Volatiles	< 0.30	%	ISO 1269

NOTE	
1.	retained on 0.020 mm sieve
2.	retained on 0.063 mm sieve

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

