

NEXUS Reprocessed HDPE 8/960 RBK

High Density Polyethylene

Nexus Resin Group, LLC.

Message:

Injection grade High Density Polyethylene
Black Reprocessed Pellets

General Information			
Recycled Content	Yes		
Appearance	Black		
Forms	Pellets, Reprocessed		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.962	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	32.1	MPa	ASTM D638
Tensile Elongation (Break)	800	%	ASTM D638
Flexural Modulus	1550	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT