

Sinvicomp SRG5540

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SRG5540 is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion.

Important attributes of Sinvicomp SRG5540 are:

Chemical Resistant

Good Stiffness

Typical application of Sinvicomp SRG5540: Engineering/Industrial Parts

| General Information | | | |
|---|----------------|-------------------|-------------|
| Features | Good Stiffness | | |
| | Oil Resistant | | |
| Uses | Gaskets | | |
| Forms | Pellets | | |
| Processing Method | Extrusion | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.30 | g/cm ³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A) | 67 | | ASTM D2240 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength ¹ (Yield) | 17.7 | MPa | ASTM D638 |
| Tensile Elongation ² (Break) | 220 | % | ASTM D638 |
| Thermal | Nominal Value | Unit | Test Method |
| Thermal Stability ³ (190°C) | > 50 | min | BS 2782 |
| NOTE | | | |
| 1. | 250 mm/min | | |
| 2. | 250 mm/min | | |
| 3. | Congo Red | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT