

# Globalene® PT331M

Polypropylene Homopolymer  
Lee Chang Yung Chemical Industry Corp.

Message:

Globalene® PT331M is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific or North America for injection molding. Important attributes of Globalene® PT331M are:

- Clarity
- Good Processability
- High Stiffness
- Homopolymer

Typical applications include:

- Caps/Lids/Closures
- Consumer Goods
- Containers
- Household Applications

General Information			
Features	Good Moldability		
	High Clarity		
	High Stiffness		
	Homopolymer		
Uses	Closures		
	Food Containers		
	Household Goods		
	Toys		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.901	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	14	g/10 min	ASTM D1238
Molding Shrinkage - Flow	1.3	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	105		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	39.2	MPa	ASTM D638
Tensile Elongation (Yield)	6.0	%	ASTM D638
Flexural Modulus	1960	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	22	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature	126	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

