

TABOREN EC 59 C 50

Linear Low Density Polyethylene

SILON s.ro

Message:

TABOREN EC 59 C 50 is a Linear Low Density Polyethylene product filled with 50% calcium carbonate. It can be processed by film extrusion and is available in Asia Pacific or Europe. Typical application: Film. Primary characteristic: antioxidant.

General Information			
Filler / Reinforcement	Calcium Carbonate,50% Filler by Weight		
Additive	Antioxidant		
Features	Antioxidant		
Uses	Film		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.36	g/cm ³	ISO 1183
Apparent Density	0.76	g/cm ³	ISO 60
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	6.0	g/10 min	ISO 1133
Additional Information	Nominal Value	Unit	Test Method
DF Test	0.0100	bar/g	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

