## **Fixmaster Epoxy Corrosion Coating**

## Epoxy; Epoxide

Loctite<sup>®</sup>

## Message:

Fixmaster Epoxy Corrosion Coating is an Epoxy; Epoxide (Epoxy) product filled with ceramic bead. It is available in North America. Applications of Fixmaster Epoxy Corrosion Coating include coating applications and food contact applications. Characteristics include: Corrosion Resistant Good Adhesion

General Information			
Filler / Reinforcement	Ceramic Bead		
Features	Bondability		
	Good Corrosion Resistance		
Uses	Protective Coatings		
Agency Ratings	USDA Unspecified Approval		
Appearance	Grey		
Forms	Pellets		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore D)	85		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.5	MPa	ASTM D638
Compressive Strength	82.7	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	15 to 20	min	
Demold Time (25°C)	240	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

