Sylvin 2910-45 Clear

Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Mechanical

Elastomers

Tear Strength

Melting Temperature

Thermal

Tensile Strength

Tensile Elongation (Break)

Sylvin 2910-45 Clear Is A Vinyl Compound Formulated With FDA Sanctioned Ingredients And A Non Phthalate Plasticizer For Extrusion Or Injection Molding Applications.

General Information			
Additive	Plasticizer		
Features	Non-Phthalate Plasticizer		
Agency Ratings	FDA Unspecified Rating		
Appearance	Clear/Transparent		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	45		ASTM D2240

Unit

MPa

Unit

kN/m

Unit °C

%

Test Method

ASTM D638

ASTM D638

Test Method

ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is
strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any
infringement occurs, please contact us immediately.

Nominal Value

Nominal Value

Nominal Value

149 to 160

7.58

450

21.9

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

