

Pro-fax SC973

Polypropylene Impact Copolymer

LyondellBasell Industries

Message:

Pro-fax Ultra SC973 high melt flow, fully formulated impact polypropylene copolymer is available in pellet form. This resin is typically used in thin-wall injection molding applications and offers excellent stiffness.

For regulatory compliance information see Pro-fax Ultra SC973 Product Stewardship Bulletin (PSB).

General Information			
Additive	Nucleating agent		
	Antistatic property		
	Moderate smoothness		
Features	Nucleated		
	Rigid, good		
	Impact copolymer		
	Antistatic property		
	High liquidity		
	Moderate smoothness		
Uses	Thin wall parts		
	Thin wall container		
	Media packaging		
	Container		
	Food container		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792B
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	110	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	28.0	MPa	ASTM D638
Tensile Elongation (Yield)	5.0	%	ASTM D638
Flexural Modulus - 1% Secant ²	1490	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	32	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	116	°C	ASTM D648

NOTE

- | | |
|----|------------|
| 1. | 50 mm/min |
| 2. | 1.3 mm/min |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

