

TABOND 5009

Polypropylene Copolymer

SILON s.ro

Message:

Tabond 5009 is a chemically modified Polypropylene. This grade is for coextrusion coating of multilayer film to give adhesion between the layers.

| General Information | | | |
|---|-----------------------|-------------------|-------------|
| Features | Copolymer | | |
| | Durable | | |
| | Good Adhesion | | |
| Uses | Adhesives | | |
| | Bonding | | |
| | Plastics Modification | | |
| Appearance | White | | |
| Forms | Pellets | | |
| Processing Method | Coextrusion | | |
| Physical | Nominal Value | Unit | |
| Density | 0.905 | g/cm ³ | |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 11 | g/10 min | |
| Thermal | Nominal Value | Unit | Test Method |
| Melting Temperature | 143 | °C | DSC |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT