

Ablebond 933-1

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablebond 933-1 is an Epoxy; Epoxide (Epoxy) material. It is available in North America for encapsulating. Primary attribute of Ablebond 933-1: Moisture Resistant.
Typical application of Ablebond 933-1: Coating Applications

General Information			
Features	Moisture Resistant		
Uses	Coating Applications		
Forms	Pellets		
Processing Method	Encapsulating		
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	124	°C	ASTM E1356
Thermoset	Nominal Value	Unit	
Pot Life	7200	min	
Shelf Life (-40°C)	52	wk	
Demold Time			
125°C	120	min	
150°C	30	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT