

# ICORENE® 9033 BA8

Polyethylene

ICO Polymers SA, A Division of A. Schulman

## Message:

ICORENE® 9033 BA8 is a Polyethylene product. It can be processed by rotational molding and is available in Latin America.

Characteristics include:

Eco-Friendly/Green

Good Adhesion

General Information			
Features	Expandable		
	Foamable		
	Good Adhesion		
	Recyclable Material		
Appearance	Natural Color		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density			ASTM D1505
-- <sup>1</sup>	0.120	g/cm <sup>3</sup>	
--	0.935	g/cm <sup>3</sup>	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	4.2	g/10 min	ASTM D1238
Aging	Nominal Value	Unit	Test Method
Accelerated Aging	5.5	month	ASTM G26
NOTE			
1.	Final		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT