

Weatherflex™ CS1522WX NTL01B

Flexible Polyvinyl Chloride

Colorite Polymers

Message:

Weatherflex™ CS1522WX NTL01B is a Flexible Polyvinyl Chloride product. It can be processed by wire & cable extrusion and is available in Asia Pacific, Europe, or North America. Typical application: Wire & Cable.

Characteristics include:

Chemical Resistant

Flame Retardant

Good Flexibility

Wear Resistant

General Information			
Features	Flame Retardant		
	Good Abrasion Resistance		
	Good Chemical Resistance		
	Low (to None) Lead Content		
	Low Smoke Emission		
	Low Temperature Flexibility		
Uses	Flexible Cord Insulation		
	Flexible Cord Jacketing		
	Wire & Cable Applications		
Processing Method	Wire & Cable Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	64		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	12.4	MPa	ASTM D412
Tensile Elongation (Break)	460	%	ASTM D412
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-60.0	°C	ASTM D746
Maximum Operating Temperature	105	°C	ASTM D2863
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	31	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

