CEPLA CE-462TB

Polypropylene

CEPLA Co., LTD

Message:

CEPLA CE-462TB is a Polypropylene material filled with filler. It is available in Asia Pacific, Europe, or Latin America.

Important attributes of CEPLA CE-462TB are:

Good Weather Resistance

Impact Resistant

Typical application of CEPLA CE-462TB: Automotive

General Information			
Filler / Reinforcement	Filler		
Features	Good Weather Resistance		
	High Impact Resistance		
Uses	Automotive Applications		
	Automotive Bumper		
	Fascias		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	27	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	65		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	15.2	MPa	ASTM D638
Flexural Modulus	1320	MPa	ASTM D790
Flexural Strength	23.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature	112	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

