

Alkatuff® LL0228

Linear Low Density Polyethylene

Qenos Pty Ltd

Message:

LL0228 is a non-pigmented linear low density hexene co-polymer, developed as a resin for use in non-standard pipe applications. LL0228 contains antioxidants to protect it during extrusion and end use.

LL0228 has been designed for extrusion into a range of non-standard pipe products. LL0228 is not designed for use in pressure applications. Addition of a UV stabilizer should be considered where the intended application involves intermittent to extended exposure to sunlight. Suitability for use in any application should be determined by appropriate performance testing.

General Information	
Additive	Antioxidant
Features	Antioxidant
	Copolymer
	Hexene Comonomer
Uses	Piping
Appearance	Natural Color
Processing Method	Extrusion
	Pipe Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.921	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.7	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT