

Karina ICE PVC COMP -E 551-28/ 60-F-IS-AS

Flexible Polyvinyl Chloride

Karina Ind. e Com. de Plásticos Ltda

Message:

FLEXIBLE (ICE COLOR) PVC COMPOUND - HIGH LIGHT RESISTANCE RECOMMENDED FOR EXTRUSION OF PROFILES - DEVELOPED FOR WINDOW CITY UNDER GG 3034 D55 SAMPLE.

General Information			
Uses	Profiles		
	Windows & Doors		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Density ¹	1.31 to 1.37	g/cm ³	IEC 60811-1-3
Color	OK		ME 12
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	53 to 57		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	> 6.86	MPa	IEC 60811-1-1
Tensile Strain (Yield)	> 250	%	IEC 60811-1-1
NOTE			
1.	24 hr		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT