

# DIGITALWAX® DC 100

Unspecified

DWS Systems

## Message:

Photosensitive Resin for DigitalWax® J Series Stereolithography Systems

DC100 Casting Resin was specially developed for direct investment casting of jewelry models. DC100 Casting Resin allows the building of detailed parts with high quality resolution, dimensional accuracy and smooth surfaces which do not require any other manual finishing.

DC100 Casting Resin is suitable for direct casting of jewelry models. Models made of DC100 Casting Resin have perfectly stable and accurate shapes and dimensions.

### Features

Smooth surface

High resolution

High accuracy

No further manual finishing needed

General Information		
Features	Good Surface Finish	
Uses	Jewelry	
	Modeling Material	
	Mold Making	
Appearance	Transparent - Slight Yellow	
Forms	Liquid	
Processing Method	3D Printing, Stereolithography	
Physical	Nominal Value	Unit
Viscosity <sup>1</sup> (25°C)	400 to 600	mPa · s
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	74	
Mechanical	Nominal Value	Unit
Flexural Modulus	286	MPa
Flexural Strength	18.6	MPa
NOTE		
1.	Liquid Resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT