

# Devcon Epoxy Coat™ 7000 Non-VOC

Epoxy; Epoxide

Devcon

Message:

A 100% solids, 2-component, self-leveling, high impact, high abrasion floor coating with a chemical-resistant finish

Intended Use:

Ideal floor coating for smooth or mildly spalled concrete (for high gloss finish); rebuild floors; protect floors from chemical attack

Product Features:

Extremely durable

Produces a level, high-gloss finish

High build (8-10 mils)

General Information			
Features	Impact resistance, high		
	Good wear resistance		
Uses	Coating application		
Appearance	Light gray		
Physical	Nominal Value	Unit	Test Method
Solid content-by Volume	100	%	
Temperature Resistance			
Dry	82	°C	
Wet	43	°C	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	85		ASTM D2240
Thermoset	Nominal Value	Unit	
Thermoset Components			
	Mixing ratio by weight: 3.2		
Component a	Mixing ratio by capacity: 2.1		
	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by capacity: 1.0		
Pot Life (24°C)	55	min	
Thermoset Mix Viscosity	2000	cP	
Additional Information	Nominal Value	Unit	
Cured 7 days @ 75°F			
Uncured Properties	Nominal Value	Unit	
Curing Time	24	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

