

apilon 52bio® DB 22

Thermoplastic Polyurethane Elastomer (Polyester)

API SpA

Message:

apilon 52bio®DB 22 is a thermoplastic polyurethane elastomer (polyester)(TPU-polyester) product. It can be processed by injection molding and is available in Europe. Typical application areas are: engineering/industrial accessories. The main features are: environmental protection/green.

General Information			
Features	Updatable resources		
	Recyclable materials		
Uses	overmolding		
Appearance	Natural color		
Forms	Particles		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.13	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	77 - 83		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	> 30.0	MPa	ASTM D638
Tensile Elongation (Break)	> 650	%	ASTM D638
Abrasion Resistance		mm ³	DIN 53516
Renewable Content	39	%	
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	> 60.0	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT