

Dutral® PM 8273

Ethylene Propylene Diene Terpolymer

Versalis S.p.A.

Message:

Dutral ® PM 8273 is a masterbatch based on Ethylene - Propylene elastomer produced by suspension polymerisation using a Ziegler-Natta Catalyst. A non-staining antioxidant is added during the production process.

Key Features

Dutral® elastomers are characterized by excellent resistance to ageing and weathering, good resistance to both high and low temperatures, low permanent set values, good resistance to a large number of chemicals.

Dutral® PM 8273 is a masterbatch suitable for the polyolefins modification, especially medium flow PP (MFI (230 °C/2.16 kg) = 10-20 g/10 mins).

Main Applications

Polymer modification.

General Information		
Additive	Antioxidant	
Features	Antioxidant	
	Good Chemical Resistance	
	Good Weather Resistance	
	High Heat Resistance	
	Low Temperature Resistant	
Uses	Masterbatch	
	Plastics Modification	
Forms	Pellets	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR) (230°C/5.0 kg)	2.4	g/10 min
Ash Content	< 3.0	wt%
Pellet Size ¹	450.0	mg
Volatiles	< 0.2	wt%
NOTE		
1.	wt of 30 pellets	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT