# Flexane® Fast Cure Rubber Repair Liquid

### Polyurethane

#### Devcon

### Message:

A fast-curing, trowelable liquid urethane for repairing rubber equipment and filling expansion joints.

Intended Use

Repair worn or damaged rubber equipment; form protective linings in equipment subject to wear, impact, abrasion, vibration, expansion, and contraction.

Product Features:

400 ml reusable cartridge

Tack-free in 30 minutes

Fast, easy, no-mess dispensing

Thorough mixing of two components with automatic mix nozzle

General Information				
Features	Fast curing			
Uses	Fill application			
	Repair Materials			
Appearance	Grey			
Forms	Liquid			
Physical	Nominal Value	Unit	Test Method	
Specific Volume	0.957	cm³/g		
Solid content-by Volume	100	%		
Abrasion Loss	330	mg/1000 cycles		
Maximum Operating Temperature				
Dry	82	°C		
Wet	49	°C		
Molding Shrinkage - Flow	0.18	%	ASTM D2566	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	94		ASTM D2240	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Strength	22.8	MPa	ASTM D412	
Tensile Elongation (Break)	450	%	ASTM D412	
Tear Strength	75.3	kN/m	ASTM D624	
Electrical	Nominal Value	Unit	Test Method	
Dielectric Strength	14	kV/mm	ASTM D149	
Thermoset	Nominal Value	Unit		
Thermoset Components				
Resin	Mixing ratio by weight: 80	Mixing ratio by weight: 80		
Hardening method	Mixing ratio by weight: 20	Mixing ratio by weight: 20		
Pot Life (24°C)	8.0	min		
Thermoset Mix Viscosity	5800	сР		

#### Additional Information

Cured 7 days @ 75°F

Uncured Properties	Nominal Value	Unit
Curing Time	2.0	hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

