

Arak HDPE BL1

High Density Polyethylene

Shazand (Arak) Petrochemical Corporation

Message:

BL1 is a high density polyethylene grade, suitable for blow moulding applications.

Characteristics:

Good flow ability.

Typical applications are:

Milk bottles.

Shakers for powders.

* BL1 is suitable for food contact.

General Information			
Features	Food Contact Acceptable		
	Good Flow		
Uses	Blow Molding Applications		
	Bottles		
Processing Method		Blow Molding	
Physical	Nominal Value	Unit	Test Method
Density	0.952	g/cm ³	DIN 53479
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	6.0	g/10 min	DIN 53735
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength	> 3.9	kJ/m ²	DIN 53453
Optical	Nominal Value	Unit	Test Method
Yellowness Index	< 4.0	YI	DIN 6167

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT