

PONACOM PE 8425

High Density Polyethylene

Ponachem Compound GmbH

Message:

PONACOM PE 8425 is a High Density Polyethylene product. It can be processed by injection molding and is available in Europe.

General Information			
Appearance	Black		
Forms	Granules		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.958 to 0.962	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR)			ISO 1133
190°C/2.16 kg	8.0	g/10 min	
190°C/5.0 kg	25 to 30	g/10 min	
Carbon Black Content	> 1.0	%	
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	62 to 65		ISO 868

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

